

CLAIMS

Please amend the claims as follows.

1. (Currently Amended) A server ~~for transmitting stored data to a network~~, comprising:
a transmit buffer for transmitting ~~the~~ a plurality of frames of stored data to ~~the~~ a network;
a network bandwidth monitor for monitoring a bandwidth of the network preceding each frame transmission; and
a transcoder for transcoding ~~the stored data~~ a frame into a reduced data content ~~frames~~ frame if the monitored bandwidth for the corresponding frame transmission is less than a first preset value, the transcoding capable of that increase increasing a rate that ~~the~~ each reduced data content ~~frames~~ frame ~~are~~ is transmitted from the buffer over the network for the corresponding monitored bandwidth.
2. (Previously Presented) The server of claim 1, wherein the transcoder increases the rate that the frames are transmitted above a receiver play out rate for a period of time after the monitored bandwidth of the network rises above the first preset value.
3. (Original) The server of claim 1, further comprising:
a redundancy encoder for redundancy encoding the transcoded data if the monitored bandwidth is less than a second preset value.
4. (Original) The server of claim 3, wherein the monitoring means includes
a control unit for activating the redundancy encoder when the monitored bandwidth is less than the second preset value.
5. (Original) The server of claim 4, wherein the first preset value equals the second preset value.
6. (Original) A server for transmitting data to a network, comprising:
transmitting means for transmitting the data to the network;

monitoring means for monitoring a bandwidth of the network;
transcoding means for transcoding the data if the monitored bandwidth is less than a first preset value; and
redundancy encoding means for redundancy encoding the transcoded data prior to transmission if the monitored bandwidth is less than a second preset value.

7. (Previously Presented) The server of claim 6, wherein the first preset value is a streaming media play out rate and the second preset value is a network available bandwidth value where some frames carrying the data are dropped by the network.

8. (Original) The server of claim 6, further comprising:
a control unit for activating the transcoding means when the monitored bandwidth is less than the first preset value and for activating the redundancy encoding means when the monitored bandwidth is less than the second preset value.

9. (Original) The server of claim 8, wherein the first preset value equals the second preset value.

10. (Previously Presented) An article comprising: a storage medium, said storage medium having stored thereon instructions for a server to transmit a portion of streaming media to a network, that, when executed by a computing device, result in:

~~transmitting the portion to the network;~~
monitoring a bandwidth of the network; and
transcoding the portion ~~prior to transmitting~~ if the monitored bandwidth is less than a first preset value, the transcoding to increase a rate that streaming media ~~frames~~ portions are transmitted over the network in relationship to the monitored bandwidth for each portion; and
transmitting the portion to the network.

11. (Original) The article of claim 10, further comprising:
activating a transcoder when the monitored bandwidth is less than the first preset value.

12. (Original) The article of claim 10, further comprising:
redundancy encoding the transcoded portion if the monitored bandwidth is less than a second preset value.
13. (Original) The article of claim 10, further comprising:
activating a redundancy encoder when the monitored bandwidth is less than the second preset value.
14. (Currently Amended) A method for a server to transmit a portion of streaming media to a network comprising:
~~transmitting the portion to the network;~~
monitoring an amount of available bandwidth on the network for the transmission of the portion; and
transcoding a reduced portion of the streaming media into frames ~~prior to transmitting~~ when the monitored bandwidth is less than a first preset value causing the frames to be transmitted over the network at an increased rate in relationship to the amount of available bandwidth for each frame; and
transmitting the portion to the network.
15. (Previously Presented) The method of claim 14 including:
maintaining the transcoding for a selected period of time after the monitored available bandwidth rises above the first preset value causing the frames to be transmitted above a streaming media play out rate; and
discontinuing the transcoding after the selected period of time so that the frames are transmitted at the media play out rate.
16. (Original) The method of claim 14, further comprising:
redundancy encoding the transcoded portion if the monitored bandwidth is less than a second preset value.

17. (Previously Presented) The method of claim 16 including setting the first preset value at a media stream play out rate and setting the second preset value at an available network bandwidth value where some frames are dropped by the network.

18. (Currently Amended) A system for a server to transmit ~~a portion of~~ streaming media to a network comprising:

means for transmitting the streaming media comprising a plurality of portions ~~the portion~~ to the network;

means for monitoring a bandwidth of the network preceding the transmission of each portion; and

means for transcoding ~~the a~~ portion prior to transmitting if responsive to the monitored bandwidth for the corresponding transmission of the portion is less than a first preset value.

19. (Currently Amended) The system of claim 18, further comprising:

means for activating a transcoder when the monitored bandwidth is less than ~~the a~~ first preset value.

20. (Previously Presented) The system of claim 18, further comprising:

means for redundancy encoding the transcoded portion if the monitored bandwidth is less than a second preset value.

21. (Currently Amended) The system of claim 18 20, further comprising:

means for activating a redundancy encoder when the monitored bandwidth is less than the second preset value.